

# Kodak PIXPRO

Digital Cameras

**ASTRO ZOOM AZ361**



## FEATURES:

Discover the new KODAK PIXPRO collection of digital cameras and discover a world of creativity at your fingertips. The AZ361 is one long zoom camera that captures life's moments big or small. Powerful features and an intuitive design set this camera apart. KODAK PIXPRO Digital Cameras. Tell your story.

- 36X Optical Zoom
- 24mm Wide Angle
- 16MP
- 3" LCD
- 720p HD Video
- OIS
- Li-ion Battery



Images are simulated.

Available Colors:   

**36X**  
OPTICAL  
ZOOM

**24mm**  
WIDE

**16MP**

**3"**  
7.6cm

**HD**

Panorama  
Capture

# Kodak

## PIXPRO AZ361

Digital Cameras

**36X**  
OPTICAL  
ZOOM

**24mm**  
WIDE

**16MP**

**3"**  
**7.6cm**

**HD**

Panorama  
Capture

### SPECIFICATIONS

### AZ361

Effective Image Sensor Pixels	16.15 Megapixels
Total Image Sensor Pixels	16.44 Megapixels [1/2.3"(CCD) ]
Lens	
Focal Length	4.3 mm (Wide) — 154.6 mm (Tele)
[ 35mm film equivalent ]	[24 mm (Wide) — 864 mm (Tele)]
F number	F2.9 (Wide) — F5.7 (Tele)
Lens Construction	14 groups 16 elements
Optical Zoom	36x
Focusing Range	Normal: (Wide) 60 cm - ∞, (Tele) 290 cm - ∞ Macro: 5 cm - ∞ (Wide Only)
Viewfinder	No
Anti-Handshake	Optical Image Stabilization
Digital Zoom	4x Digital Zoom (Combined Zoom: 144x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP:3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	720p30, 720p15, VGA, QVGA
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	Movie Format: MOV (H.264), Audio: G.711 [Monaural]
Shooting Modes	Auto, P, S, A, M, Face Beauty, Panorama, SCN [ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Sketch, Snow, Children, ID, Glass, Photo Frame, Panning Shot, Text, Portrait, Fish Eye, Party, Indoor, Leaf Museum, Night Portrait, Pet, (Dog), Pet (Cat)], Movie, CS
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement
HDR	Yes
Panorama	0° - 180° (Horizontal)
LCD Display	3.0 inch (460K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/1600/3200 (4M)
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/2000 - 30 Seconds
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Date Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K)
Flash	
Flash Method	Pop-up
Flash Modes	Auto, Red-Eye Reduction, Forced Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 4.4 m (ISO800)
Recording Media	Internal Memory: Approx. 25MB SD/SDHC Card (Up to 32GB Support) [Nonsupport MMC Card]
Other Features	PictBridge, ExifPrint Support, Multi-Language Support (27 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D)
Eye-Fi Support	Yes
Power	Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 200 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 0 - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 112.7 x 81.6 x 76.7 mm (Based on CIPA Standards)
Weight	Approx. 416g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, AC Adapter, USB Cable, Shoulder Strap, Lens Cover, CD-ROM, Service Card, Quick Start Guide Warranty

To learn more about KODAK PIXPRO Digital Cameras:  
visit: [www.kodakcamera.jkilt.com](http://www.kodakcamera.jkilt.com)

JK Imaging, Ltd.  
1411 W. 190th Street, Suite 550  
Gardena, CA 90248

**JK Imaging Ltd.**

**Kodak** Licensed Product

© 2013 JK Imaging, Ltd. The Kodak trademark and trade dress are used under license from Kodak.  
All information contained in this document is subject to change without notice.  
Document Number/Sequence: U.DIS.001.0001.0313.en.01

